

LED LINEAR LIGHT

Products Advantage:

- SAMSUNG/ EPISTAR LED, high luminous efficiency, up to 100lm/w;
- The linear light adopt high purity aluminum lamp body, with ideal lighting distribution curve, perfect light transmittance property, effectively restrain glare, oxidation corrosion resistance and cooling effect;
- Easy to install and operate lifespan more than 50,000hrs;
- Environment protection: no UV, no IR, meet RoHs requirements;
- Energy saving 70% or more energy compared with T5/T8 fluorescent lamp;
- Low power consumption and environment friendly.

Application:

- Residential/Institution Buildings;
- Conference/Meeting rooms;
- Factories&offices;
- Commercial Purposes;
- Schools, colleges&Universities;
- Hospitals;
- Hotel;
- Other Lighting;



Product Specifications:

Model No.	Power	Length	Size	Lumen Efficacy	FP	IP	beam angle	CCT
NTE-XT3F-20W-F	20W	0.9M	900*75*54	>100lm/w	>0.95	IP20	120	3000-6500K
NTE-XT3F-30W-F	30W	0.9M	900*75*54	>100lm/w	>0.95	IP20	120	3000-6500K
NTE-XT4F-40W-F	40W	1.2M	1190*75*54	>100lm/w	>0.95	IP20	120	3000-6500K
NTE-XT5F-60W-F	60W	1.5M	1490*75*54	>100lm/w	>0.95	IP20	120	3000-6500K